FUJIFILM

FINEPIX A345 ZOOM

DIGITAL CAMERA

If affordable digital cameras normally mean cheap build quality, then the A345 Zoom breaks the mould. Four megapixels and a sharp 3x optical zoom lens are housed within this compact, solid piece of engineering. Truly a no-fuss piece of equipment.

4 MP | 1.7" LCD | 3x OPTICAL | 3.6x DIGITAL | xD-Picture Card

>> Key Features

- 4.1 million effective pixels
- High quality 1.7-inch LCD monitor
- 3x optical zoom lens
- One-touch, fully automatic operation, with easy navigation
- Highly efficient energy consumption: uses 2x AA alkaline batteries (or rechargeable batteries)
- Movie capture at 15 frames per second
- PictBridge™-compatible for direct PC-free printing

DEDICATED ACCESSORIES

- Soft case for FinePix A345 Zoom

UNIVERSAL ACCESSORIES

- xD-Picture Card™ up to 1GB
- DPC-AD PC card adapter for xD-Picture Card™
- DPC-CF CompactFlash™ adapter for xD-Picture Card™
- DPC-UD1 USB Pen Drive
- 2HR-3UF Rechargeable AA-type Ni-MH battery
- Ultra-fast charger & 6x 2100mAh Ni-MH batteries
- BK-NH standard battery charger & 2x 1700 Ni-MH batteries
- Fujifilm overnight charger & 4x 1800mAh Ni-MH batteries

INCLUDED ACCESSORIES

- 16MB xD-Picture Card™
- 2x AA alkaline batteries
- Wrist strap
- USB cable
- Owner's manual
- CD-ROM for Windows® and Macintosh®
  - USB driver
  - FinePix Viewer v. 4.3

Number of effective pixels	4.1 million
CCD sensor	1/2.5 inch CCD
Number of recorded pixels	3.98 million pixels (2304x1728) 1.92 million (1600x1200) 1.2 million (1280x960) 3.1 million (640x480)
File format	JPEG (Exif Ver 2.2)
Movie format	AVI (Motion JPEG)
Storage media	xD-Picture Card™

Number of images (Approximately)

Mode	16MB	32MB	64MB	128MB	256MB	512MB
4M	7	18	32	64	129	259
2M	25	50	101	204	409	818
1M	33	68	137	275	550	1101

Movie (Approx. no. in Min/Sec) — **Standard Movie**/Number of minutes

320	65s	130s	4.3m	8.6m	17.3m	34.6m
160	260s	8.6m	17.3m	34.6m	69.3m	138.6m

Lens	Fujinon 3x 35-105mm (35mm equivalent)
Aperture	F2.8 to F4.7 (automatically selected)
Viewfinder	Real image optical viewfinder (75% coverage)
Digital zoom	3.6x
Exposure	Program AE
Flash	Auto, forced, red-eye reduction, slow sync suppressed, red-eye reduction + slow sync
LCD monitor	1.7-inch TFT (115,000 pixels) (approx 90% coverage)
Video output	NTSC/PAL selectable
Interface	USB, Video connection
Power source	2x AA batteries (Alkaline or Ni-MH) AC power adapter (optional)
Dimensions	90 x 60 x 30.3 mm
Weight	132g

Product Code TBC
Barcode TBC

>> TECHNICAL SPECIFICATIONS

PictBridge

Specifications are subject to change without notice. All trademarks are the property of their respective holders.